

Ombre


BASIC INFORMATION

Launch Date	01/04/2019	Tariff item number	54079300
Delivery time (weeks) special lab dip	3	Number of colour ways	5
Country of origin	Turkey	Characteristics	Sheer
Vertical repeat (cm)	37.00	Vertical repeat (inch)	14.57
Horizontal repeat (cm)	48.50	Horizontal repeat (inch)	19.09
Roll diameter (in cm, for 50 meters)	0	Roll diameter (in inch, for 50 meter)	0
Double folded face in	Yes	Minimum for special colour (m)	500
Average piece length (m)	50	MID	TRMAR3INE

CATEGORY

Colouring type	Yarn dyed	Treatment	Washed
Type of print/dye - disperse	Yes	Zinc selvedge	Yes
After treatment - zinc selvedge weight (g/m)	22	After treatment - none	Yes

Care codes

Care code for washing (°C)	Wash at 71°C	Care code for washing (°F)	Wash at 160°F
   			

Use codes

Use code - curtains/draperies	Yes	Maritime	Yes
-------------------------------	-----	----------	-----

FABRIC TYPE

Composition	100% Polyester inherent FR	Average yarn number	161.54
Weaving type - jacquard	Yes	Construction	60x45
Useable width (cm)	300.00	Useable width (inch)	118.11
Full width (cm)	302	Full width (inch)	118.9
Woven	Yes	Weight (g/m ²)	65

FR STANDARDS

AATCC 96 (Complies)	Yes	AS/NZS 1530.2 (Pass)	Yes
AS/NZS 1530.3 (Pass)	Yes	BS5867 part 2 type B	Yes
BS5867 part 2 type C (Complies)	Yes	Boston Fire test BFD IX-1 (Pass)	Yes
CAL 19 section 1237.1	Yes	DIN 4102 (B1)	Yes
EN13773	Yes	FMVSS 302 (Pass)	Yes
IMO FTPC PART 7: Textiles and films	Yes	Japanese L1091	Yes

M1 France	Yes	NFPA 701	Yes
NY/NJ Port Authority - FAR 25.853 12 (Pass)		SN 198'898 (Class 5.2)	Yes
	Yes		

ENVIRONMENTAL STANDARDS

Oeko-Tex	Yes
----------	-----

SPECIFICATIONS

Colour fastness to light	6	Wyzenbeek wire screen (double rubs - residential use, stopped after 15 000 double rubs)	15,000
Acoustic absorption ISO 354 - ISO 11654	E/NA	Wyzenbeek wire screen heavy duty	Yes

Colour fastness to light - ISO 105-B02

Colour fastness to light	6
--------------------------	---

Colour fastness to water - ISO 105-E01

Colour fastness to water	5
--------------------------	---

Resistance to domestic washing 40°C (indicated in %) - ISO 6330

Dimensional change warp	0.33	Dimensional change warp after ironing	0.93
Dimensional change weft	0.23	Dimensional change weft after ironing	0.13
Colour fastness (ISO 105 C06)	5		

Resistance to domestic washing 60°C (indicated in %) - ISO 6330

Dimensional change warp	0.16-	Dimensional change warp after ironing	1.11-
Dimensional change weft	0.59-	Dimensional change weft after ironing	0.00
Colour fastness (ISO 105 C06)	5		

Resistance to dry cleaning P (indicated in %) - ISO 105 D01

Dimensional change warp	0.00	Dimensional change warp after ironing	0.00
Dimensional change weft	0.00	Dimensional change weft after ironing	0.00

Dimensional stability (indicated in %) - ISO 3759

Dimensional change warp	0.38-	Dimensional change warp after ironing without steam	0.13
Dimensional change warp after ironing with steam		Dimensional change weft	0.57-

	0.33		
Dimensional change weft after ironing without steam		Dimensional change weft after ironing with steam	
	0.20-		0.07

CONSTRUCTION

Yarn 1

Warp composition	100% Polyester inherent FR	Warp yarn sizes	20DN
Warp threads per cm	60.00	Warp turns per meter (TPM)	0
Warp type filament	Yes		
Warp specification not textured	Yes	Warp not high tenacity	Yes

Yarn 2

Weft composition	100% Polyester inherent FR	Weft yarn sizes	70DN-80NE
Weft threads per cm	45.00	Weft turns per meter (TPM)	0
Weft type staple	Yes	Weft type filament	Yes
Weft specification not napped	Yes	Weft specification not textured	Yes
Weft not high tenacity	Yes		