Jager



BASIC INFORMATION

Launch Date	01/04/2017	Tariff item number	55151290
Delivery time (weeks) special lab dip	4	Number of colour ways	4
Country of origin	Turkey	Characteristics	Jacquard
Vertical repeat (cm)	32.00	Vertical repeat (inch)	12.60
Horizontal repeat (cm)	35.00	Horizontal repeat (inch)	13.78
Roll diameter (in cm, for 50 meters)	0	Roll diameter (in inch, for 50 meter)	0
Face in	Yes	Minimum for special colour (m)	1000
Average piece length (m)	50	MID TRT	EXTRABUR

CATEGORY

Colouring type	Yarn dyed	Treatment	Thermofixed
After treatment - none	Yes		

Care codes

Care code for washing (°F)

Wash at 140°F gentle cycle













Use codes

Use code - curtains/draperies	Yes	Maritime	Yes
Use code - accessories	Yes		

FABRIC TYPE

Composition	100% Polyes	ster inherent FR	Average yarn number	57.3
Weaving type - j	acquard	Yes	Construction	66x40
Useable width (c	em)	142.00	Useable width (inch)	55.91
Full width (cm)		144	Full width (inch)	56.69
Woven		Yes	Weight (g/m²)	185

FR STANDARDS

1

AATCC 96 (Complies)	Yes	AS/NZS 1530.2 (Pass)	Yes
AS/NZS 1530.3 (Pass)	Yes	BS5867 part 2 type B	Yes
BS5867 part 2 type C (Complies)	Yes	Boston Fire test BFD IX-1 (Pass)	Yes
CAL 19 section 1237.1	Yes	CAN/ULC-S109 Large flame test	Yes
CAN/ULC-S109 Small flame test	Yes	DIN 4102 (B1)	Yes

Technical Product Summary: Jager

Technical Product Summary



EN13773 Yes FMVSS 302 (Pass) Yes IMO FTPC PART 7: Textiles and films Yes Japanese L1091 Yes M1 France Yes NFPA 701 Yes NY/NJ Port Authority - FAR 25.853 12 (Pass) SN 198'898 (Class 5.2) Yes

Yes

UNI 9174 Classe Uno (Pass) Yes

UNI 9174 Classe Uno (Pass)	Yes		
ENVIRONMENTAL STANDAF	RDS		
Oeko-Tex	Yes	ISO 14001	Yes
SPECIFICATIONS			
Colour fastness to light	6	Pilling	3
Brush pilling	3	Acoustic absorption ISO 354 - ISO 11654 draped	4 C/flat D
Colour fastness to light - ISO 105-l	B02		
Colour fastness to light	6		
Colour fastness to water - ISO 105	-E01		
Colour fastness to water	5		
Colour fastness to dry rub - ISO 10)5-X12		
Colour fastness dry rub	4-5		
Colour fastness to wet rub - ISO 1	05-X12		
Colour fastness wet rub	4-5		
Elongation - ISO 13934-1			
Elongation warp (%)	31	Elongation weft (%)	20.5
Resistance to domestic washing 4	0°C (indicated i	n %) - ISO 6330	
Dimensional change warp	0.93-	Dimensional change warp after ironing	0.86-
Dimensional change weft Colour fastness (ISO 105 C06)	0.40- 5	Dimensional change weft after ironing	0.47-



0.00

Resistance to domestic washing 60°C (indicated in %) - ISO 6330

Dimensional change warp Dimensional change weft Colour fastness (ISO 105 C06)	1.60- 0.77- 5	Dimensional change warp after ironing Dimensional change weft after ironing	1.46- 0.73-
Resistance to dry cleaning P (indic	cated in %) - ISC	0 105 D01	
Dimensional change warp Dimensional change weft Colour fastness (ISO 105 D01)	0.76- 0.36- 5	Dimensional change warp after ironing Dimensional change weft after ironing	0.93- 0.40-
Dimensional stability (indicated in	%) - ISO 3759		
Dimensional change warp	0.02	Dimensional change warp after ironing w	ithout steam 0.20
Dimensional change warp after ironin	g with steam	Dimensional change weft	0.08-

0.00

Dimensional change weft after ironing with steam

CONSTRUCTION

Dimensional change weft after ironing without steam

Yarn 1			
Warp composition 100% Polyester	r inherent FR	Warp yarn sizes	20d
Warp threads per cm	66.00	Warp turns per meter (TPM)	NA
Warp type filament	Yes		
Warp specification textured	Yes	Warp not high tenacity	Yes
Yarn 2			
Weft composition 100% Polyester	r inherent FR	Weft yarn sizes	300d
Weft threads per cm	10.00	Weft turns per meter (TPM)	100
Weft type filament	Yes		
Weft specification not textured	Yes	Weft not high tenacity	Yes
Yarn 3			
Weft composition 100% Polyester	r inherent FR	Weft yarn sizes	Ne 30/2
Weft threads per cm	10.00	Weft turns per meter (TPM)	600
Weft type staple	Yes		
Weft specification not textured	Yes	Weft not high tenacity	Yes
Yarn 4			

Technical Product Summary



Weft composition 100% Polyester	inherent FR	Weft yarn sizes	Ne 30/2
Weft threads per cm	10.00	Weft turns per meter (TPM)	600
Weft type staple	Yes		
Weft specification not textured	Yes	Weft not high tenacity	Yes
Yarn 5			
Weft composition 100% Polyester	inherent FR	Weft yarn sizes	Ne 15/1
Weft threads per cm	10.00	Weft turns per meter (TPM)	650
Weft type staple	Yes		
Weft specification not textured	Yes	Weft not high tenacity	Yes