


## 2570 Flurry

Designed as an acoustical wall panel fabric, Flurry also wears like a contract upholstery in high-traffic situations. At eye level, the 54" wall panel, upholstery and drapery fabric has the look of raw silk bouclé, but the 100% inherently fire retardant polyester construction passes ASTM E-84 (Unadhered) and NFPA 701 Test 1. Available in six neutral colorways, Flurry makes a luxurious background texture for commercial interiors.



©2017 BRENTANO, INC. PATTERN AND DESIGN

Flurry

### FABRIC INFORMATION

ACT Symbols:



Repeat:

Collection:

Affinity Collection

Cleaning:

[Fabric Care](#) » S (Solvent)

Width:

54" [ 137 cm ]

Usage:

Panel, Upholstery, Drapery

Contents:

100% FR Inherent Polyester

Weight:

14 oz [ 434.06 g/m. ]

Finish:

Note:

### TECHNICAL SPECIFICATIONS

Wear Test:

Over 30,000 Double Rubs (Wyzenbeek)

Pilling:

Class 5.0 (ASTM D3511)

Fire Resistance:

Passes NFPA 701 Small Scale, Passes California Bulletin 117E UFAC Class 1 NFPA 260 Class 1, ASTM E-84 Class A (Unadhered)

Crocking:

Dry: 5.0 Wet: 5.0 (AATCC 116-2013)

Lightfastness:

60 Hours Class 4 (AATCC 16)

Breaking Strength:

Warp: 225 lb Fill: 153 lb

Seam Slippage:

Warp: 46.1 lb Fill: 58.2 lb (ASTM D4034)