

A N D E S PRODUCT SPECIFICATIONS

Application
Upholstery

Content
100% Polyurethane (CPU) - Clean Performance Urethane

Backing
100% Polyester

Width
54"

Repeat
N/A

General Characteristics

- Abrasion: 200,000+ Double Rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis: 10+ weeks (ISO 1419)
- Colorfastness to Crocking: Grade 5 (AATCC 8)
- Colorfastness to Light: 200+ hours (AATCC-16)
- Meets all ACT Heavy Duty Performance Guidelines

Flammability

CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2

Cleaning

W, Bleach (10:1)

Environmental

- PVC/Phthalates Free
- Solvent/DMF Free
- Complies with Healthier Hospitals & Cal 01350

Country of Origin

China



Storm



Alloy



Fossil



Trail



Clay



Thrill



Quarry



Harbor



Sumatra



Graphite

Warranty

Please refer to our Terms of Sales for warranty information.

- Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.

Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.



ACT® Registered Certification Marks