

BRILLIANT PRODUCT SPECIFICATIONS

Application

Upholstery

Content

Face - 100% Silicone, Inherently Graffiti-Free®

Middle - 100% Polyurethane

Backing

100% Polyester

Width

54"

Repeat

N/A

Roll Length

App. 40 yds

General Characteristics

- Abrasion: 1,000,000+ double rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis: 10+ weeks (ISO 1419)
- Colorfastness to Crocking: Grade 5 (AATCC 8)
- Colorfastness to Light: 200+ hours (AATCC-16)
- Tearing Strength (ASTM D2262)
- Adhesion of Coating (ASTM D751)
- Meets all ACT Heavy Duty Performance Guidelines

Flammability

CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2;

Cleaning

W/S, Bleach (4:1)

Environmental

- PVC/Phthalate Free
- No added FR/Anti-Bacterial
- Healthier Hospitals Compliant
- Complies with REACH & CAL 01350



Aspen



Warranty

Please refer to our Terms of Sales for warranty information.

- Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.

Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.



ACT® Registered Certification Marks