Concertex

DELIRIUM

PRODUCT SPECIFICATIONS

Application

Upholstery

Content

100% Polyurethane

Backing

100% Polyester

Finish

Graffiti-Free®

Width

52"

Repeat

34.08" H, 9.68" V

Roll Length

App. 50 yds

General Characteristics

- Abrasion: 100,000+ double rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis: 10+ weeks (ISO 1419)
- Colorfastness to Crocking: Grade 5 (AATCC 8)
- Colorfastness to Light: 200+ hours (AATCC-16)
- Tearing Strength (ASTM D2262)
- Adhesion of Coating (ASTM D751)
- Meets all ACT Heavy Duty Performance Guidelines

Flammability


CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2

Cleaning

W/S, Bleach (4:1)

Environmental

- DMF-Free
- PVC/Phthalate Free
- No added FR/Anti-Bacterial
- Healthier Hospitals Compliant
- Complies with REACH & CAL 01350



Graphite









Copper







Warranty

Please refer to our Terms of Sales for warranty information.

 Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.
Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.