

## FLASH

### PRODUCT SPECIFICATIONS

#### Application

Upholstery

#### Content

100% Polyurethane

#### Backing

100% Polyester

#### Finish

Graffiti-Free®

#### Width

54"

#### Repeat

N/A

#### Roll Length

App. 50yds

#### General Characteristics

- Abrasion: 200,000+ Double Rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis: 10+ weeks (ISO 1419)
- Colorfastness to Crocking: Grade 5 (AATCC 8)
- Colorfastness to Light: 200+ hours (AATCC-16)
- Tearing Strength (ASTM D2262)
- Adhesion of Coating (ASTM D751)
- Meets all ACT Heavy Duty Performance Guidelines

#### Flammability

CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2

#### Cleaning

W/S, Bleach (4:1)

#### Environmental

- Healthier Hospitals Compliant
- DMF-Free
- PVC/Phthalate Free
- No added FR/Anti-Bacterial



Autumn



Snow

Fossil

Champagne

Trail

Latte



Silver

Flint

Gust

Shadow

Bluebell



Gravel

Meadow

Sizzle

Pitch

Seaweed



Deep Sea

#### Warranty

Please refer to our Terms of Sales for warranty information.

- Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.

Wyzenbeek results above 100,000 Double Rubs have not been shown to be a reliable indicator of increased fabric lifespan.



ACT® Registered Certification Marks