

INTERLOCK PRODUCT SPECIFICATIONS

Application

Upholstery

Content

100% Polyurethane

Backing

100% Polyester

Finish

Graffiti-Free®

Width

52"

Repeat

1.4375" H, 2.4375" V

General Characteristics

- Abrasion: 100,000+ Double Rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis: 10+ weeks (ISO 1419)
- Colorfastness to Crocking: Grade 5 (AATCC 8)
- Colorfastness to Light: 200+ hours (AATCC-16)
- Meets all ACT Heavy Duty Performance Guidelines

Flammability

CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2

Cleaning

W/S, Bleach (4:1)

Environmental


- DMF-Free
- Phthalate Free
- No added FR/Anti-Bacterial
- Complies with Healthier Hospitals & CAL 01350

Country of Origin

South Korea



Pine



Ivory



Oyster



Icicle



Driftwood



Rosewood



Charcoal



Night

Warranty

Please refer to our Terms of Sales for warranty information.

- Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.



ACT® Registered Certification Marks