

SEBAGO

PRODUCT SPECIFICATIONS

Application

Upholstery

Content

100% Polyurethane

Backing

100% Polyester

Finish

Graffiti-Free®

Width

54"

Repeat

N/A

Roll Length

App. 50yds

General Characteristics

- Abrasion: 200,000+ double rubs (ASTM D4157 Wyzenbeek)
- Hydrolysis: 10+ weeks (ISO 1419)
- Colorfastness to Crocking: Grade 5 (AATCC 8)
- Colorfastness to Light: 200+ hours (AATCC-16)
- Tearing Strength (ASTM D2262)
- Adhesion of Coating (ASTM D751)
- Meets all ACT Heavy Duty Performance Guidelines

Flammability

CA Bulletin 117-2013; UFAC/NFPA-260; IMO A652 (16) 8.2

Cleaning

W/S, Bleach (4:1)

Environmental

- Healthier Hospitals Compliant
- DMF-Free
- PVC/Phthalate Free
- No added FR/Anti-Bacterial



Bordeaux



White



Cloud



Mustard Seed



Md. Chocolate



Tawny



Cloud Mist



Mustard



Pecan



Blood Orange



Crimson



Persimmon



Brique



Merlot



Caspian



Burmese



Cordovan



Mocha



Chestnut



Earth



Buck



Mink



Dk.Fudge



Java



Espresso



Walnut



Meadow



Reef



Ultra Marine



S.Black



D.Black



Moonless

Warranty

Please refer to our Terms of Sales for warranty information.

- Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance.

Wyzenbeek results above 100,000 double rubs have not been shown to be a reliable indicator of increased fabric lifespan.



ACT® Registered Certification Marks